



RIGOL

# DG70000 Series

Arbitrary Waveform Generator

DataSheet

DSB13103-1110  
Sep. 2024



# DG70000 Series


## Arbitrary Waveform Generator

### Key Specifications


- Sample rates up to 5 GSa/s (12 GSa/s interpolated)
- 4-channel synchronization for a single instrument
- -70 dBc SFDR
- 16-bit vertical resolution
- 1.5 GSample waveform memory depth per channel
- Direct generation of signals with carriers up to 5 GHz
- Total jitter low as 10 ps<sub>p-p</sub>, random jitter low as 350 fs<sub>rms</sub>
- Sample rates adjustable from 100 Sa/s to 12 GSa/s
- High-precision synchronization with channel-to-channel skew repeatability low as ±10 ps

### Brand New SiFi III Technical Platform

Built on RIGOL's brand new **SiFi III** platform, the DG70000 series supports multiple signal output modes such as sequence output, precise trigger output, continuous output, and pattern jump output. With industry-leading waveform memory depth, it achieves a maximum data throughput of **38.4 Gbps**. The advanced sequence function allows for configuration of its waveform memory, which maximizes flexibility. In terms of signal processing, this series has various functions including adjustable sample rates, IQ modulation, DUP, and direct digital synthesis (DDS).



SiFi III




# DG70000 Series

## Arbitrary Waveform Generator



16-bit Vertical Resolution



Multi-channel Synchronization


-70 dBc SFDR



1.5 GHz Modulation Bandwidth

### Meeting Requirements for Various Applications

This series is customer-oriented with a variety of functions suitable for practical applications. For example, the creation of advanced sequences enables you to self-define long complex waveforms. It can realize high-precision multi-channel synchronization and the output of high-bandwidth and low-jitter waveforms, making it ready for applications in areas like communications, scientific research, and industry. Multiple standard interfaces provides you with more solutions in connectivity, realizing remote instrument control and synchronization.



Channel Setting Interface



Advanced Sequence Editing Interface

### Brand New Appearance and UI Design Bring Extraordinary User Experience

This series features a 7U full-rack structure and delicate industrial design. Equipped with two touch screens, it brings brand new UI design and extraordinary user experience. The main display is a 15.6-inch touch screen with one button electronic tilt. It supports simultaneous waveform display in multi-pane windowing, making it easier to view signals, measurements, and results.

# DG70000 Series


## Arbitrary Waveform Generator

### High Sample Rate and High Resolution, Restore Signals with High Quality

The DG70000 series provides sample rate up to **12 GSa/s** and an adjustable range from **100 Sa/s** to **12 GSa/s**. The 16-bit high resolution ensures its high fidelity.

To restore the signal with high quality is the basis for reliable and repeatable testing. The DG70000 series features excellent sample rate and resolution, capable of restoring the signal without distortion, presenting you with more real test results.

- **12 GSa/s Sample Rate**  
(5 GSa/s data rate, interpolated: 10 GSa/s for real waveform output and 12 GSa/s for IQ waveform output)
- **16-bit Vertical Resolution**



### Wider Output Frequency Range and Modulation Bandwidth Ensures Wireless Signal Simulation Test

With the renewal and iteration of wireless standards, the carrier frequency and modulation bandwidth of wireless signals are constantly improving, bringing more severe test challenges.

The DG70000 series provides up to **5 GHz** output frequency and up to **1.5 GHz** modulation bandwidth. It can directly output IQ baseband signal or use the Digital Up Converter (DUC) option to generate RF modulated signal, meeting your demands for testing various types of wireless signals.

- **Max. 5 GHz Output Frequency**
- **Max. 1.5 GHz Modulation Bandwidth**





# DG70000 Series

## Arbitrary Waveform Generator

### Lower Channel-to-Channel Delay and Channel Extension Ability, Reproduce Complex Test Scenarios

In cutting-edge fields such as quantum technology, it is necessary to build a multi-channel high-speed signal system. Such complex test scenarios require that the arbitrary waveform generator should support multi-channel signal output and low channel-to-channel delay.

The DG70000 series can realize multi-channel synchronization, and **10 ps** channel-to-channel delay of a single device, enabling you to rebuild multi-channel and low-latency complex test scenarios.

- Min. 10 ps Channel-to-Channel Delay
- Multi-channel Synchronization across Multiple Devices





### More Sample Points Help Generate Purer Signals

Simulation testing through building real-world environment can effectively reduce the cost of system testing. Improved signal purity and the creation of long complex signals are key requirements for such simulation.

The DG70000 series can provide **-70 dBc** spurious-free dynamic range (SFDR) and up to **1.5G** sample points per channel, creating long complex waveforms without compromising bandwidth. At the same time, it provides the advanced sequence function, which can divide the waveform memory to store several waveform segments, making good use of the waveform memory depth. It also makes it flexible to construct your desired waveforms through internal and external trigger events.

- 1.5 GSample Waveform Memory Depth
- -70 dBc SFDR



# Product Features

## Product Features

- Up to 5 GSa/s sample rates (12 GSa/s interpolated)
- 4-channel synchronization for a single instrument (4-channel models only)
- -70 dBc SFDR
- 16-bit vertical resolution
- 1.5 GSample waveform memory depth per channel
- Direct generation of signals with carriers up to 5 GHz
- Generate arbitrary waveforms point by point; recover the signal without distortion
- Total jitter low as 10 ps<sub>p-p</sub>, random jitter low as 350 fs<sub>rms</sub>
- Sample rates adjustable from 100 Sa/s to 12 GSa/s
- High-precision synchronization with channel-to-channel skew repeatability low as ±10 ps
- Support advanced sequence to define outputs of various complex waveforms
- Multiple interfaces available: LAN, USB3.0, HDMI
- Support the import of external waveform files
- 15.6-inch angle-adjustable display

---

Built on its unique SiFi III technical platform and Android operating system, the DG70000 series Arbitrary Waveform Generator (AWG) has the following advantages: accurate and adjustable sample rates; generate arbitrary waveforms point by point; recover the signal without distortion; etc. This series is customer-oriented with a variety of functions suitable for practical applications. For example, the creation of advanced sequences enables you to self-define long complex waveforms. The multi-channel high-precision synchronization, high-bandwidth and low-jitter waveform output make it ready for applications in a variety of industrial and communications fields. Equipped with a 15.6-inch angle-adjustable touch screen supporting multi-pane windowing, it brings a brand new UI design and extraordinary user experience. Multiple standard interfaces provide you with more solutions in connectivity, making it simple to control the instrument remotely.

---

# Specifications

Specifications are valid under the following conditions:

the instrument is within the calibration period; stored for at least two hours at 0°C to 50°C temperature; 40-minute warm-up.

Unless otherwise noted, the specifications in the manual include the measurement uncertainty.

- **Typical (typ.):** typical performance, which 80 percent of the measurement results will meet at room temperature (approximately 25°C). The data are not warranted and do not include the measurement uncertainty.
- **Nominal (nom.):** the expected mean or average performance or a designed attribute (such as the 50Ω connector). The data are not warranted and are measured at room temperature (approximately 25°C).
- **Measured (meas.):** an attribute measured during the design phase which can be compared to the expected performance, e.g. the amplitude drift varies with time. The data are not warranted and are measured at room temperature (approximately 25°C).

## NOTE:

All charts in this manual are the measurement results of multiple instruments at room temperature unless otherwise noted.

## Overview of the DG70000 Series Technical Specifications

### Overview of the DG70000 Series Technical Specifications

	DG70002	DG70004
Number of Channels	2	4
Sample Rate	100 Sa/s to 12 GSa/s <sup>[1]</sup>	
Vertical Resolution	16-bit (0 Marker/channel)	
	15-bit (1 Markers/channel)	
	14-bit (2 Markers/channel)	
Waveform Memory Depth	1.5 Gpts/channel	
Multi-channel Synchronization	Skew Repeatability	±10 ps
	Delay Adjustment Resolution	3 ps
Effective Frequency Output	The maximum frequency is determined as "sample rate/2.5".	
	2 GHz (Real Data mode)	
	4 GHz (IQ Data mode, 10 GSa/s interpolated)	

## Analog Output

Analog Output		
DC High Bandwidth Output (DC HBW)	Amplitude Range	350 mVpp to 700 mVpp (single-ended, 50 $\Omega$ terminated) <sup>[2]</sup> 700 mVpp to 1400 mVpp (differential, 100 $\Omega$ terminated)
	Amplitude Accuracy <sup>[3]</sup>	$\pm 2\%$ of the setting value
	Offset	$\pm 20$ mV (50 $\Omega$ into GND), $\pm 40$ mV into DC voltage terminated
	Offset Resolution	50 $\mu$ V (nom.)
	Offset Accuracy <sup>[4]</sup>	$\pm 2$ mV
	Analog Bandwidth	2 GHz (-3 dB), 4 GHz (-6 dB)
	Rise/Fall Time Measured at 20% to 80% Levels	<120 ps at 700 mVpp single-ended termination
DC Amplifier Output (DC AMP)	Amplitude Range	25 mVpp to 1000 mVpp (single-ended, 50 $\Omega$ terminated) 50 mVpp to 2000 mVpp (differential, 100 $\Omega$ terminated)
	Amplitude Accuracy <sup>[3]</sup>	$\pm 2\%$ of the setting value $\geq 100$ mVpp $\pm 5\%$ of the setting value < 100 mVpp
	Offset	$\pm 1$ V (50 $\Omega$ into GND), $\pm 2$ V into DC voltage terminated
	Offset Accuracy <sup>[4]</sup>	Common mode: $\pm(2\%$ of the offset + 10 mV); ((OutP + OutN)/2) Differential mode: $\pm 20$ mV; (OutP - OutN)
	Analog Bandwidth	1.3 GHz (-3 dB), 2.6 GHz (-6 dB)
	Rise/Fall Time Measured at 20% to 80% Levels	<160 ps at 1.0 Vpp single-ended
	AC Output (AC)	Amplitude Range
Amplitude Accuracy		$\pm 0.5$ dB (typ.)
Offset		$\pm 2$ V/70 mA
Offset Accuracy <sup>[4]</sup>		$\pm(2\%$ of the offset + 20 mV); into an open circuit (zero-load current)
Analog Bandwidth		10 MHz~2 GHz (-3 dB), 10 MHz~3.8 GHz (-6 dB), 10 MHz~4.8 GHz (-18 dB)
Number of Channels	2/4 channels, 3 SMA connectors per channel at front panel	

## Time Domain

Time Domain	
Bit Rate (sample rate/4 points per cycle)	Max. 1.25 Gb/s



## Time Domain

Jitter	Random Jitter	350 fs <sub>rms</sub>
	Total Jitter	10 ps <sub>p-p</sub>

## Frequency Domain

### Frequency Domain

Output Match VSWR	DC HBW	DC~4 GHz < 1.8:1
	DC AMP	DC~2.6 GHz < 1.8:1
	AC	DC~5 GHz < 2.0:1
Intermodulation Distortion	100 MHz ± 1 MHz	-70 dBc
	1 GHz ± 1 MHz	-60 dBc

## Spurious Free Dynamic Range (SFDR)

SFDR Characteristics: SFDR is determined as a function of the directly generated carrier frequency. Harmonics not included. Measured with a balun and with output amplitude set to 500 mVpp.

### SFDR DC HBW Output (Typ.)

	In Band Performance			Adjacent Band Performance	
	DC HBW Output	Measured Across	Specifications	Measured Across	Specifications
2.5 GSa/s	100 MHz	DC~500 MHz	-80 dBc	DC~1.25 GHz	-72 dBc
	DC~625 MHz	DC~625 MHz	-70 dBc	DC~1.25 GHz	-62 dBc
	DC~1 GHz	DC~1 GHz	-60 dBc	DC~1.25 GHz	-58 dBc
5 GSa/s	100 MHz	DC~1 GHz	-80 dBc	DC~2.5 GHz	-72 dBc
	DC~1.25 GHz	DC~1.25 GHz	-70 dBc	DC~2.5 GHz	-62 dBc
	DC~2 GHz	DC~2 GHz	-60 dBc	DC~2.5 GHz	-58 dBc
10 GSa/s	100 MHz	DC~1 GHz	-80 dBc	DC~5 GHz	-60 dBc
	DC~1.25 GHz	DC~1.25 GHz	-68 dBc	DC~5 GHz	-50 dBc
	DC~2 GHz	DC~2 GHz	-60 dBc	DC~5 GHz	-48 dBc
	2 GHz~3.5 GHz	2 GHz~3.5 GHz	-42 dBc	DC~5 GHz	-42 dBc
	3.5 GHz~4 GHz	3.5 GHz~4 GHz	-55 dBc	DC~5 GHz	-40 dBc
12 GSa/s	100 MHz	DC~1 GHz	-80 dBc	DC~5 GHz	-60 dBc
	DC~1.25 GHz	DC~1.25 GHz	-68 dBc	DC~5 GHz	-50 dBc
	DC~2 GHz	DC~2 GHz	-60 dBc	DC~5 GHz	-48 dBc
	2 GHz~3.5 GHz	2 GHz~3.5 GHz	-42 dBc	DC~5 GHz	-42 dBc
	3.5 GHz~4 GHz	3.5 GHz~4 GHz	-55 dBc	DC~5 GHz	-40 dBc

### SFDR DC AMP Output (Typ.)

	In Band Performance			Adjacent Band Performance	
	DC AMP Output	Measured Across	Specifications	Measured Across	Specifications
2.5 GSa/s	100 MHz	DC~500 MHz	-80 dBc	DC~1.25 GHz	-72 dBc
	DC~625 MHz	DC~625 MHz	-70 dBc	DC~1.25 GHz	-62 dBc
	DC~1 GHz	DC~1 GHz	-60 dBc	DC~1.25 GHz	-58 dBc

**SFDR DC AMP Output (Typ.)**

5 GSa/s	100 MHz	DC~1 GHz	-80 dBc	DC~2.5 GHz	-72 dBc
	DC~1.25 GHz	DC~1.25 GHz	-70 dBc	DC~2.5 GHz	-62 dBc
	DC~2 GHz	DC~2 GHz	-60 dBc	DC~2.5 GHz	-58 dBc
10 GSa/s	100 MHz	DC~1 GHz	-80 dBc	DC~5 GHz	-60 dBc
	DC~1.25 GHz	DC~1.25 GHz	-68 dBc	DC~5 GHz	-50 dBc
	DC~2 GHz	DC~2 GHz	-60 dBc	DC~5 GHz	-48 dBc
12 GSa/s	2 GHz~2.6 GHz	2 GHz~2.6 GHz	-44 dBc	DC~5 GHz	-44 dBc
	100 MHz	DC~1 GHz	-80 dBc	DC~5 GHz	-60 dBc
	DC~1.25 GHz	DC~1.25 GHz	-68 dBc	DC~5 GHz	-50 dBc
	DC~2 GHz	DC~2 GHz	-60 dBc	DC~5 GHz	-48 dBc
	2 GHz~2.6 GHz	2 GHz~2.6 GHz	-44 dBc	DC~5 GHz	-44 dBc

**SFDR AC Output (Typ.)**

	AC Output	In Band Performance		Adjacent Band Performance	
		Measured Across	Specifications	Measured Across	Specifications
2.5 GSa/s	100 MHz	DC~500 MHz	-80 dBc	DC~1.25 GHz	-72 dBc
	DC~625 MHz	DC~625 MHz	-70 dBc	DC~1.25 GHz	-62 dBc
	DC~1 GHz	DC~1 GHz	-60 dBc	DC~1.25 GHz	-58 dBc
5 GSa/s	100 MHz	DC~1 GHz	-80 dBc	DC~2.5 GHz	-72 dBc
	DC~1.25 GHz	DC~1.25 GHz	-70 dBc	DC~2.5 GHz	-62 dBc
	DC~2 GHz	DC~2 GHz	-58 dBc	DC~2.5 GHz	-58 dBc
10 GSa/s	100 MHz	DC~1 GHz	-80 dBc	DC~5 GHz	-60 dBc
	DC~1.25 GHz	DC~1.25 GHz	-68 dBc	DC~5 GHz	-50 dBc
	DC~2 GHz	DC~2 GHz	-58 dBc	DC~5 GHz	-46 dBc
	2 GHz~3.5 GHz	2 GHz~3.5 GHz	-46 dBc	DC~5 GHz	-42 dBc
	3.5 GHz~4 GHz	3.5 GHz~4 GHz	-46 dBc	DC~5 GHz	-40 dBc
12 GSa/s	100 MHz	DC~1 GHz	-80 dBc	DC~5 GHz	-60 dBc
	DC~1.25 GHz	DC~1.25 GHz	-68 dBc	DC~5 GHz	-50 dBc
	DC~2 GHz	DC~2 GHz	-58 dBc	DC~5 GHz	-46 dBc
	2 GHz~3.5 GHz	2 GHz~3.5 GHz	-46 dBc	DC~5 GHz	-42 dBc
	3.5 GHz~4 GHz	3.5 GHz~4 GHz	-46 dBc	DC~5 GHz	-40 dBc

**Harmonics and Phase Noise****Harmonics****Harmonic Distortion (@ 500 mVpp)**

SHG (Differential or with a balun)	10 MHz~500 MHz	< -62 dBc
	500 MHz~1 GHz	< -50 dBc
	1 GHz~4 GHz	< -30 dBc
SHG (Single-ended)	10 MHz~500 MHz	< -42 dBc
	500 MHz~1 GHz	< -40 dBc
	1 GHz~4 GHz	< -25 dBc

## Harmonics

THG	10 MHz~750 MHz	< -55 dBc
	750 MHz~1 GHz	< -50 dBc
	1 GHz~2 GHz	< -35 dBc

## Harmonic Distortion (@ 1000 mVpp)

SHG (Differential or with a balun)	10 MHz~500 MHz	< -55 dBc
	500 MHz~1 GHz	< -45 dBc
	1 GHz~2.6 GHz	< -35 dBc
SHG (Single-ended)	10 MHz~500 MHz	< -38 dBc
	500 MHz~1 GHz	< -30 dBc
	1 GHz~2.6 GHz	< -25 dBc
THG	10 MHz~500 MHz	< -33 dBc
	500 MHz~1 GHz	< -30 dBc
	1 GHz~2.6 GHz	< -25 dBc

## Phase Noise

Output Phase Noise Typ. <sup>[5]</sup>	fc=100 MHz: -126 dBc/Hz @ offset 10 kHz
	fc=1 GHz: -112 dBc/Hz @ offset 10 kHz
	fc=2 GHz: -106 dBc/Hz @ offset 10 kHz
	fc=4 GHz: -100 dBc/Hz @ offset 10 kHz

## Input

### Input

Trigger In	Inputs	2
	Polarity	Positive or Negative
	Impedance	1 M $\Omega$ (nom.)
	Range	1 M $\Omega$ : $\pm 8 V_{rms}$
	Threshold Level	Range: -5.0 V to 5.0 V Resolution: 0.1 V (nom.)
	Trigger Pulse Width <sup>[6]</sup>	20 ns
	Minimum Trigger Interval	10 $\mu s$
Modulating Signal Input	Trigger Sensitivity	500 mVpp
	Connector	SMA (rear panel)
	Inputs	4
	Multiplexing	Analog modulation input or baseband IQ input
	Frequency Range	DC~100 MHz
	Input Level	1 Vpp (full-range)
	Impedance	50 k $\Omega$ (nom.)
Connector	SMA (rear panel)	

## Input

Pattern Jump Input	Input Impedance	1 k $\Omega$ to GND
	Input Level	3.3 V LVCMOS
	Number of Destinations	256
	Strobe Polarity	Negative or positive edge (selectable)
	Strobe Setup Time	5 ns
	Strobe Hold Time	5 ns
	Strobe Minimum Pulse Width	64 ns
	Analog Output Channel Delay	<12,500/sample rate
	Connector	DB15 female (rear panel)

## Pattern Jump Pin Assignments

Pin	Description	Pin	Description	Pin	Description
1	GND	6	GND	11	Data bit 5, input
2	Data bit 0, input	7	Strobe, input	12	Data bit 6, input
3	Data bit 1, input	8	GND	13	Data bit 7, input
4	Data bit 2, input	9	GND	14	GND
5	Data bit 3, input	10	Data bit 4, input	15	GND

## Waveform Capability

### Waveform Capability

Waveform File Import Capability	*.txt file format, supporting voltage code and normalized value
	*.wfm file format created by RIGOL AWG
	*.seq file format created by RIGOL AWG

Waveform File Export Capability	*.txt file format, supporting voltage code and normalized value
	*.wfm file format created by RIGOL AWG
	*.seq file format created by RIGOL AWG

## Marker Output

### Marker Output

Number	0 (default), 1, or 2
Min. Pulse Width	3.2 ns
Max. Data Rate	2.5 GSa/s
Type	Single-ended
Impedance	50 $\Omega$ (nom.)



## Marker Output

	Window: -0.5 V to 1.75 V
Output into 50 $\Omega$	Amplitude: 400 mV to 1.75 V (typ.)
	Resolution: 100 $\mu$ V (nom.)

Rise Time	(20%~80%): 750 ps
Delay Control	$\pm$ 2 ns
Connector	SMA (rear panel)

## Sequencer

### Sequencer

Sequence	Number of steps for each sequence: 1 to 16,384
Subsequence	Number of steps for each subsequence: 1 to 16,383
Waveform Segment	Waveform length: 2.4k to 500M sample points (1.5G optional) Minimum waveform granularity: 1 sample point
Output Sequence	Execute the steps of the sequence/subsequence in specific order.
Loop	Execute 1 to $2^{32}-1$ times or infinite times in loop.
Jump	Wait: wait for a trigger event to play the step in the sequence Synchronous Jump: support synchronous event jump to a specified step in the sequence Asynchronous Jump: support asynchronous event jump to a specified step in the sequence Go To: define the next step in the sequence or subsequence to go to and play Pattern Jump: support pattern jump for sequence steps (256 jump destinations)

## Clock Characteristics

### Clock Characteristics

10 MHz Reference Clock Output	Output Amplitude	+4 dBm $\pm$ 2 dB
	Output Frequency	10 MHz $\pm$ (1 ppm + aging)
	Temperature Stability	< 0.5 ppm (0°C to 50°C, with the reference 25°C)
	Aging Rate	< 1 ppm/year
	Output Impedance	50 $\Omega$ (nom.)
Sample Clock Output	Output Amplitude	+2 dBm to +10 dBm
	Output Frequency	2.5 GHz~6 GHz
	Output Impedance	50 $\Omega$ (nom.)

## Clock Characteristics

Sync Clock Output	Output Amplitude	1.0 V $\pm$ 150 mVpp to 50 $\Omega$
	Output Frequency	Sample clock frequency/32
	Output Impedance	50 $\Omega$ (nom.)
Reference Clock Input	Input Amplitude	-5 dBm to +5 dBm
	Fixed Frequency	10 MHz, $\pm$ 40 Hz
	Variable Frequency Range	35 MHz~150 MHz
	Input Impedance	50 $\Omega$ (nom.)
External Sample Clock Input	Input Amplitude	0 dBm to +10 dBm
	Input Frequency	2.5 GHz~6.0 GHz
	Input Impedance	50 $\Omega$ (nom.)
Connector	SMA (rear panel)	

### NOTE:

[1] 5 GSa/s data rate, interpolated: 10 GSa/s for real waveform output; 12 GSa/s for IQ waveform output.

[2] It is recommend to connect the output terminal that is not in use to GND with a 50  $\Omega$  load.

[3] 100 MHz sine waveform

[4] It is under the condition that the self-calibration temperature is within 25°C $\pm$ 5°C indoor temperature.

[5] 5 GHz sample clock with 10 GSa/s sample rate

[6] Nominal value with 5 GHz sample clock. Reference formula: 48/Sample Clock + 10 ns.

# General Specifications

## Characteristics

Characteristics	
Operating System	Android
Touch Screen	15.6" main screen, 3.5" auxiliary screen

## Interface

Interface	
LAN Interface	1 at rear panel, RJ-45 Ethernet connector, 10/100/1000BASE-T port, supporting LXI-C
Web Control	Support Web Control (input the IP address of the generator into the Web browser to display the operation interface)
HDMI Interface	1 at rear panel, HDMI 1.4b, A plug; used to connect to an external monitor or projector
USB 3.0 Host High-Speed Interface	4 (2 at front panel and 2 at rear panel)
USB 3.0 Device High-Speed Interface	1 at rear panel, supporting TMC
Sync Control Interface	1 at rear panel, MDR-26 interface, used to control the synchronization of multiple instruments

## Power Supply

Power Supply	
AC Input	100 V to 240 V (nom.)
AC Frequency	45 Hz to 440 Hz
Consumption	300 W (typ.), 500 W (max.)

## Environment

Environment		
Temperature Range	Operating	0°C~+50°C
	Non-operating	-30°C~+70°C

## Environment

Humidity Range	Operating	below +30°C: ≤90% RH (without condensation)
		+30°C to +40°C, ≤75% RH (without condensation)
		+40°C to +50°C, ≤45% RH (without condensation)
	Non-operating	below 65°C: ≤90% RH (without condensation)
Altitude	Operating	below 3,000 meters
	Non-operating	below 15,000 meters

## Regulation Standards

### Regulation Standards

Electromagnetic Compatibility	Compliant with EMC Directive (2014/30/EU), compliant with or higher than the standards specified in EN 61326-1:2013, EN 61326-2-1:2013, EN IEC 61000-3-2:2019+A1, EN 61000-3-3:2013+A1:2019	
	CISPR 11:2009+A1 Class A	
	EN IEC 61000-3-2:2019+A1	Harmonics, Class A
	EN 61000-3-3:2013+A1:2019	Voltage flicker
	EN 61000-4-2:2009	±4.0 kV (contact discharge), ±8.0 kV (air discharge)
	EN 61000-4-3:2006+A1+A2	10 V/m (80 MHz to 1 GHz); 3 V/m (1.4 GHz to 6 GHz)
	EN 61000-4-4:2004+A1	2 kV power cord
	EN 61000-4-5:2006	1 kV (phase-to-neutral voltage); 2 kV (phase-to-earth voltage); 2 kV (neutral-to-earth voltage)
	EN 61000-4-6:2009	10V, 0.15 MHz to 80 MHz
	EN 61000-4-11:2004	Voltage dip: 0% UT during half cycle; 0% UT during 1 cycle; 70% UT during 25 cycles Short interruption: 0% UT during 250 cycles
Safety	EN 61010-1:2010+A1:2019	
	IEC 61010-1:2010+A1:2016	
	UL 61010-1: 2012 R7.19	
	CAN/CSA-C22.2 NO. 61010-1-12 + G11 + G12 (R2017) + A1	
Vibration	Meets GB/T 6587; class 2 random	
	Meets MIL-PRF-28800F and IEC60068-2-6; class 3 random	



## Regulation Standards

Shock	Meets GB/T 6587-2012; class 2 random
	Meets MIL-PRF-28800F and IEC 60068- 2- 27; class 3 random
	(in non-operating conditions: 30 g, half sine, 11 ms duration, 3 shocks along the main axis, a total of 18 vibrations)

## Mechanical Characteristics

### Mechanical Characteristics

Dimension	439 mm (W) x 310 mm (H) x 491 mm (D)
-----------	--------------------------------------

Weight	Package excluded: <22.5 kg
--------	----------------------------

Package included: <29.5 kg
----------------------------

## Warranty and Calibration Interval

### Warranty and Calibration Interval

Warranty	Three years for the mainframe, excluding the accessories.
----------	---

Recommended Calibration Interval	12 months
----------------------------------	-----------

# Order Information and Warranty Period

## Order Information

---


Order Information	Order No.
<b>Model</b>	
4-channel, 2 GHz bandwidth, 5 GSa/s data rate, 1.5G sample points	DG70004
2-channel, 2 GHz bandwidth, 5 GSa/s data rate, 1.5G sample points	DG70002
<b>Standard Shipped Accessory</b>	
Power cord (based on destination country)	— —
USB cable	— —
Three 50 $\Omega$ , 18 GHz SMA terminators per channel	— —
<b>Performance Upgrade Option</b>	
Digital Up Converter (DUC) and IQ Modulation	DG70000-DIGUP
Complex Sequence Function	DG70000-SEQ
High-speed Serial Function	DG70000-PJ
DC Amplifier Output	DG70000-DC
Multitone & Chirp Mode	DG70000-MTONENL

## Warranty Period

---

Three years for the mainframe, excluding the accessories.

# Option Ordering and Installation Process




1. According to the usage requirements, please purchase the specified function options from **RIGOL Sales Personnel**, and provide the serial number of the instrument that needs to install the option.
2. After receiving the option order, the **RIGOL** factory will mail the paper software product entitlement certificate to the address provided in the order.
3. Log in to **RIGOL** official website for registration. Use the software key and instruments serial number provided in the entitlement certificate to obtain the option license code and the option license file.

# Boost Smart World and Technology Innovation


Industrial Intelligent  
Manufacturing



Semiconductors



Education &  
Research



Communication



System Integration



New Energy



- Cellular-5G/WIFI
- UWB/RFID/ ZIGBEE
- Digital Bus/Ethernet
- Optical Communication

- Digital/Analog/RF Chip
- Memory and MCU Chip
- Third-Generation Semiconductor
- Solar Photovoltaic Cells

- New Energy Automobile
- PV/Inverter
- Power Test
- Automotive Electronics

*Provide Testing and Measuring Products  
and Solutions for Industry Customers*

## HEADQUARTER

**RIGOL TECHNOLOGIES CO., LTD.**  
No.8 Keling Road, New District,  
Suzhou, JiangSu, P.R.China  
Tel: +86-400620002  
Email: info@rigol.com

## JAPAN

**RIGOL JAPAN CO., LTD.**  
5F, 3-45-6, Minamiotsuka, Toshima-Ku,  
Tokyo, 170-0005, Japan  
Tel: +81-3-6262-8932  
Fax: +81-3-6262-8933  
Email: info.jp@rigol.com

## EUROPE

**RIGOL TECHNOLOGIES EU GmbH**  
Carl-Benz-Str.11  
82205 Gilching  
Germany  
Tel: +49(0)8105-27292-0  
Email: info-europe@rigol.com

## KOREA

**RIGOL KOREA CO., LTD.**  
5F, 222, Gonghang-daero,  
Gangseo-gu, Seoul, Republic of Korea  
Tel: +82-2-6953-4466  
Fax: +82-2-6953-4422  
Email: info.kr@rigol.com

## NORTH AMERICA

**RIGOL TECHNOLOGIES, USA INC.**  
10220 SW Nimbus Ave.  
Suite K-7  
Portland, OR 97223  
Tel: +1-877-4-RIGOL-1  
Fax: +1-877-4-RIGOL-1  
Email: info@rigol.com

**RIGOL®** is the trademark of **RIGOL TECHNOLOGIES CO., LTD.** Product information in this document is subject to update without notice. For the latest information about **RIGOL's** products, applications and services, please contact local **RIGOL** channel partners or access **RIGOL** official website: [www.rigol.com](http://www.rigol.com)